

## Fully Automatic Blood Pressure Monitor



## **Features**

- Easy to Use Fully Automatic
- Easy to Read LCD Display
- Clinically Validated for Use
- 90 Reading Memory with Date and Time
- Measures on Inflation
- Universal Cuff (22cm-42cm)











## **Specifications**

Model Number	TMB-1970	CL
Power supply	Battery powered mode 6V DC 4x AAA batteries	AIR HOSE —
Display mode	Digital LCD display V.A.52 mm × 58 mm	AINTIOGE
Measurement mode	Oscillographic testing mode	AIR CONNECTOR
Measurement range	Rated cuff pressure: 0 mmHg~299 mmHg	
Accuracy	Measurement pressure: SYS: 60 mmHg~230 mmHg	
	DIA: 40 mmHg~130 mmHg Pulse value: (40-199) beat/minute	
Normal working condition	A temperature range of : +5°C to +40°C A relative humidity range of 15% to	
	90%, non-condensing, but not requiring a water vapour partial	pressure
	greater than 50 hPa An atmospheric pressure range of : 700 hPa	Pa to 1060 hPa
Storage & Transportation	Temperature: -20°C to +60°C A relative humidity range of ≤ 93%	6,
condition	non-condensing, at a water vapour pressure up to 50 hPa	
Net weight	Approx.198 g (Excluding the batteries)	
External Dimensions	Approx.102 mm × 107 mm × 40 mm	
Attachment	4× AAA batteries, user manual	
Mode of operation	Continuous operation	
Degree of protection	IP21	
against ingress of water		

## **Structure**

